4488WRA 4 TONNE **'RAILS, WHEEL ALIGN WIDE'** FOUR POST HOIST

POST HEIGHT 2110 mm

10741 WIDTH 3367 MM

PRODUCT SPECIFICATIONS

HOIS

~

5086 mm

6350

FOOTPENTLENCH

FRODUCT SPECIFICATIONS	K
Footprint	3267 x 6356 mm (including run-ups, extended)
Length	5086 mm
Width	3267 mm
Height	2110 mm
Width Between Posts	2700 mm
Width Between Platforms	943 mm
Platform Length	4580 mm
Platform Width	520 mm
Run-Up Length	945 mm extendable to 1270 mm
Motor	3 Phase, 3 HorsePower, 415 Volt * (requires 3 Phase and Earth, 5 Amp)
Lifting Capacity	4 tonnes
Maximum Raised Height	1675 mm
Minimum Lowered Height	170 mm
Minimum Lifting Time	24 seconds
Concrete Depth	min 100 mm, mesh reinforced, min strength 25 MPa
Hydraulic Oil	high quality, 46 weight, anti-wear
Gross Weight	1420 kg
Shipping Dimensions	5.0 x 1.15 x 0.6 metres
Finish	powder coated for added durability
Warranty	3 years

Features	
Wheel Turntable Position	wheel alignment recess for turntable positioning (includes removable cover plate)
Operational	40mm incremental height adjustment
	push button to lift; lever to lower
	4 beam pads included – J3BP
Safety	deadman controls (automatic stop when released)
	protection for cable breakage, overload and hydraulic failure
Service & Installation	comprehensive service manuals and installation instructions included
Customisation	
	control unit position
Colour	extensive range of powder coated colours available
4488WRA-240VOLT *	optional single phase, 240 Volt motor (requires 240 Volts under load at motor, hard wired on 20 Amp circuit)
Extra Long	1metre longer (6086 mm platforms)
Optional Accessories	
LJB-04	Slip Plates (pair) for vehicles with independent rear suspension
EXT-PAD	Beam Riser, Standard (for additional pick-up points)
EXT-PAD-LOW	Beam Riser, Lowered (for low profile vehicles)
AXLE-PU	Beam Riser, Axle (attach to rails for stable axle pick-up)
PL92-RB	Rubber Block, Standard (for cushioned lifting)
PL92-RB-40	Rubber Block, Low Profile (for low profile vehicles)
SL02-Nest	Rubber Block Nest
7252-023-01-A	Jack Stand, Wide (insert between platforms; turn upside down for a tool tray)

RECESS DEPTH 50 mm

As the policy of Molnar Hoists is one of continuous improvement, the manufacturer reserves the right to change specifications without notice.



For more information, please contact us or your local Molnar Representative

T 08 7120 8700 F 08 8346 0097 E sales@molnarhoists.com.au www.molnarhoists.com.au

7210 mm

est.

onwards & upwards