## 4 TONNE **'RAILS, WIDE'** FOUR POST HOIST

POST HEIGHT 2110 mm

POTAL WIDTH 3361 MM

## HOISTS

na menome some of

.086

హా

FOOTPRINTLENC

<b>PRODUCT SPECIFICATIONS</b>	sunue 210	
Footprint	3267 x 6356 mm (including run-ups, extended)	
Length	5086 mm	
Width	<b>3267</b> mm	
Height	2110 mm	
Width Between Posts	2700 mm	
Width Between Platforms	943 mm	
Platform Length	4580 mm	
Platform Width	520 mm	
Run-Up Length	945 mm extendable to 1270 mm	
Motor	<b>3 Phase, 3 HorsePower, 415 Volt *</b> (requires 3 Phase and Earth, 5 Amp)	
Lifting Capacity	4 tonnes	
Maximum Raised Height	1675 mm	
Minimum Lowered Height	170 mm	
Minimum Lifting Time	24 seconds	
Concrete Depth	min 100 mm, mesh reinforced, min strength 25 MPa	
Hydraulic Oil	high quality, 46 weight, anti-wear	
Gross Weight	1440 kg	
Shipping Dimensions	5.0 x 1.15 x 0.6 metres	
Finish	powder coated for added durability	
Warranty	3 years	

Features	
Extra Wide	ideal for servicing trade vehicles, vans, four-wheel-drives or small trucks 'wheels free'
Operational	40mm incremental height adjustment
	push button to lift; lever to lower
	4 beam pads included – J3BP
Safety	deadman controls (automatic stop when released)
	protection for cable breakage, overload and hydraulic failure
Service & Installation	comprehensive service manuals and installation instructions included
CUSTOMISATION	
	control unit position
Colour	extensive range of powder coated colours available
4488RA-240VOLT *	<b>optional single phase, 240 Volt motor</b> (requires 240 Volts under load at motor, hard wired on 20 Amp circuit)
Extra Long	1metre longer (6086 mm platforms)
Optional Accessories	
EXT-PAD	Beam Riser, Standard (for additional pick-up points)
EXT-PAD-LOW	Beam Riser, Lowered (for low profile vehicles)
AXLE-PU	Beam Riser, Axle (attach to rails for stable axle pick-up)
PL92-RB	Rubber Block, Standard (for cushioned lifting)
PL92-RB-40	Rubber Block, Low Profile (for low profile vehicles)
SL02-Nest	Rubber Block Nest
7252-023-01-A	Jack Stand, Wide (insert between platforms; turn upside down for a tool tray)

As the policy of Molnar Hoists is one of continuous improvement, the manufacturer reserves the right to change specifications without notice.



For more information, please contact us or your local Molnar Representative

T 08 7120 8700 F 08 8346 0097 E sales@molnarhoists.com.au www.molnarhoists.com.au

1270

## onwards & upwards