

FEATURES

3267 x 5924 mm (including run-ups)
4982 mm
3267 mm
2110 mm
2700 mm
943 mm
4580 mm
520 mm
1180 mm
3 Phase, 3 HorsePower, 415 Volt * (requires 3 Phase and Earth, 5 Amp)
4 tonnes
1675 mm
170 mm
24 seconds
min 100 mm, mesh reinforced, min strength 25 MPa
high quality,46 weight, anti-wear
1020 kg
5.0 x 0.95 x 0.6 metres
powder coated for added durability
3 years

As the policy of Molnar Hoists is one of continuous improvement, the
manufacturer reserves the right to change specifications without notice.
manajactarer reserves the right to change specifications without notice.

Wheel Turntable Position	wheel alignment recess for turntable positioning (includes removable cover plate)
Operational	40mm incremental height adjustment
	push button to lift; lever to lower
	single lever locks all four posts
Safety	deadman controls (automatic stop when released)
	protection for cable breakage, overload and hydraulic failure
Service & Installation	comprehensive service manuals and installation instructions included
Customisation	
	control unit position
Colour	extensive range of powder coated colours available
4488WA-EL-240VOLT **	optional single phase, 240 Volt motor (requires 240 Volts under load at motor, hard wired on 20 Amp circuit)
Extra Long	1metre longer (5982 mm platforms)
OPTIONAL ACCESSORIES	
JB11A	Air Jacking Beam, Wide (for wheel free service options
LJB-04	Slip Plates (pair) for vehicles with independent rear suspension
4488-S/W-66	Four Post Run-Ups, Short (815 mm)
4488-S/W-66EL	Four Post Run-Ups, Long (1190 mm)
7252-023-01-A	Jack Stand, Wide (insert between platforms; turn upside down for a tool tray)



For more information, please contact us or your local Molnar Representative

T 08 7120 8700 F 08 8346 0097 E sales@molnarhoists.com.au www.molnarhoists.com.au

onwards & upwards