

Designed to supplement the Molnar Hoist range, these lifting aids will improve workshop efficiency and safety

LIFTING AID ACCESSORIES

**M
O
L
N
A
R**



HOISTS

EP10



Provides valuable extra clearance for four-wheel-drives and vans

Length	160 mm
Width	160 mm
Height - min	180 mm
Height - max	225 mm

'EXTENSION PAD'

For use on:

- Two Post Hoist Base
- Two Post Hoist All Rounder
- Two Post Hoist Asymmetric
- Two Post Hoist Four Tonne

JB11 & JB11A



Raise a vehicle for wheel free service options

	JB11	JB11A
Width	1100 mm	1200 mm
Max span	1275 mm	<
Min height	75 mm (above platform)	
Max height	310 mm (above platform)	

'AIR JACKING BEAM'

For use on:

- Four Post Hoists

JB11A

Wide version for 'A' series

Refer Air Jacking Beam Accessories brochure for related accessories

PL92-RB & PL92-RB-40



Solid rubber block for cushioned lifting

	PL92-RB	PL92-RB-40
Length	150 mm	150 mm
Width	100 mm	110 mm
Height	70 mm	40 mm

'RUBBER BLOCKS'

For use on:

- Platform Lift
- Scissor Lift
- Quick Lift
- Rubber Block Nest

SLO2-NEST



Nest to house rubber blocks

Length	160 mm
Width	100 mm
Height	120 mm

'RUBBER BLOCK NEST'

For use on:

- Four Post Rails Hoists
- Air Jacking Beam
- Scissor Lift with beam
- Quick Lift with beam

JJ3 & J3



Support and stabilises vehicle

	JJ3	J3
Diameter	140 mm	100 mm
Height - min	30 mm	30 mm
Height - max	80 mm	80 mm

'PICK-UP PADS'

For use on:

- Two Post Hoist Base
- Two Post Hoist All Rounder
- Two Post Hoist Asymmetric
- Two Post Hoist Four Tonne

J3BP



Stabilises vehicles on beams

Made from solid, long-lasting vulcanised rubber

Diameter	90 mm
Pad Height	30 mm

'BEAM PAD'

For use on:

- Four Post Rails Hoists
- Air Jacking Beam
- Scissor Lift with beam
- Quick Lift with beam



EXT-PAD



Provides valuable extra clearance for four-wheel-drives and vans

Length	120 mm
Width	100 mm
Height - min	170 mm
Height - max	215 mm

'BEAM RISER, STANDARD'

For use on:

- Four Post Rails Hoists
- Air Jacking Beam
- Quick Lift with beam
- Scissor Lift with beam

EXT-PAD-LOW



For vehicles with low clearance

Length	120 mm
Width	100 mm
Height - min	140 mm
Height - max	175 mm

For use on:

- Four Post Rails Hoists
- Air Jacking Beam
- Quick Lift with beam
- Scissor Lift with beam

'BEAM RISER, LOWERED'

AXLE-PU



For stable pick-up on axle; cradle head prevents lateral movement

Length	120 mm
Width	100 mm
Height - min	150 mm
Height - max	205 mm

For use on:

- Four Post Rails Hoists
- Air Jacking Beam
- Quick Lift with beam
- Scissor lift with beam

'BEAM RISER, AXLE'

PL92-10



Provides valuable extra clearance for four-wheel-drives and vans

Length	120 mm
Width	100 mm
Height - min	155 mm
Height - max	195 mm

For use on:

- Platform Lift

'PLATFORM RISER'

SLO2-SB



Provides more pick-up options

Length	1550 mm
Width	270 mm
Height	55 mm

For use on:

- Scissor Lift

'SCISSOR LIFT BEAM'

QLSB-02



Provides more pick-up options

Length	1550 mm
Width	270 mm
Height	110 mm

For use on:

- Quick Lift

'QUICK LIFT BEAM'

7252-023-01 & 7252-023-01A



Insert between platforms; can be turned upside down and used as a tool tray

	7252-023-01	7252-023-01A
Length	1045 mm	1145 mm
Width	225 mm	<
Height	60 mm	<

For use on:

- Four Post Hoists
 - Four Post Rails Hoists
- 7252-023-01A**
Wide version for 'A' series

'JACK STAND'

As the policy of Molnar Hoists is one of continuous improvement, the manufacturer reserves the right to change specifications without notice.

For more information, please contact us or your local Molnar Representative

T 08 7120 8700 F 08 8346 0097
E sales@molnarhoists.com.au
www.molnarhoists.com.au

onwards & upwards

